




# Shandong Xiangyue bearing Trading Co....



NU2330EMA Bearing 2D drawings and 3D CAD models

5.906 Inch | 150 Millimeter x 12.598 Inch | 320 Millimeter x 4.252 Inch | 108 Millimeter Timken NU2330EMA Cylindrical Roller Bearing

Bearing No. NU2330EMA

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	43.49
EAN	0087796300989
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity   Plain Inner Ring   2 Rib Outer Ring   Cage on Outer Ring ID
Long Description	150MM Bore; Straight Bore Profile; 320MM Outside Diameter; 108MM Width;



## Shandong Xiangyue bearing Trading Co....

	Brass Cage Material; RBEC 1   ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium In
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	<a href="http://www.timken.com">http://www.timken.com</a>
Manufacturer Item Number	NU2330EMA
Weight / LBS	95.8
B	4.252 Inch   108 Millimeter
d	5.906 Inch   150 Millimeter
D	12.598 Inch   320 Millimeter
Design Units	METRIC
Bearing Weight	43.600 Kg
Type	NU
Tapered Bore	N
d - Bore	150 mm
D - Outer Diameter	320.000 mm
C - Inner Ring Width	108.000 mm
B - Outer Ring Width	108.000 mm
C0 - Static Radial Rating	1620000 N
C - Dynamic Radial Rating <sup>1</sup>	1330000 N
Reference Thermal Speed Rating (Grease)	1300
Reference Thermal Speed Rating (Oil) <sup>2</sup>	1500
Cg - Geometry Factor <sup>3</sup>	0.1347
R - Inner Ring To Clear Radius <sup>4</sup>	3.0 mm
r - Outer Ring To Clear Radius <sup>5</sup>	3.0 mm



## Shandong Xiangyue bearing Trading Co....

da - Inner Ring Backing Diameter	183.000 mm
Da - Outer Ring Backing Diameter	0.000 mm