





TYPE TS



Timken 397 394D Tapered roller bearing

Bearing No. 397

397 Bearing 2D drawings and 3D CAD models

Series	395
Cone Part Number	397
Design Units	Imperial
Cage Type	Stamped Steel
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions) ¹	38700 lbf
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions) ²	10000 lbf
d	2.3622 in
B - Cone Width	0.8660 in
R - Cone Backface To Clear Radius ³	0.03 in
da - Cone Frontface Backing Diameter	2.68 in
db - Cone Backface Backing Diameter	2.72 in
Ab - Cage-Cone Frontface Clearance	0.11 in
Aa - Cage-Cone Backface Clearance	0.05 in
a - Effective Center Location ⁴	-0.03 in
C90 - Dynamic Radial Rating (90 million revolutions) ⁵	5760 lbf
C1 - Dynamic Radial Rating (1 million revolutions) ⁶	22200 lbf
C0 - Static Radial Rating	28100 lbf



Shandong Xiangyue bearing Trading Co....

C_{a90} - Dynamic Thrust Rating (90 million revolutions) ⁷	3970 lbf
K - Factor ⁸	1.45
G1 - Heat Generation Factor (Roller-Raceway)	56
G2 - Heat Generation Factor (Rib-Roller End)	21.4
Cg - Geometry Factor	0.0984