



TYPE TS



Timken 28995 28921D Tapered roller bearing

Bearing No. 28995

28995 Bearing 2D drawings and 3D CAD models

|   |               |
|---|---------------|
| Series  | 28900         |
| Cone Part Number  | 28995         |
| Design Units  | Imperial      |
| Cage Type   | Stamped Steel |
| C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions) <sup>1</sup>      | 41500 lbf     |
| C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions) <sup>2</sup> | 10800 lbf     |
| d   | 2.4700 in     |
| B - Cone Width  | 1.0000 in     |
| R - Cone Backface To Clear Radius <sup>3</sup>                                | 0.14 in       |
| da - Cone Frontface Backing Diameter  | 2.76 in       |
| db - Cone Backface Backing Diameter   | 3.03 in       |
| Ab - Cage-Cone Frontface Clearance  | 0.09 in       |
| Aa - Cage-Cone Backface Clearance   | 0.05 in       |
| a - Effective Center Location <sup>4</sup>                                    | -0.1 in       |
| C90 - Dynamic Radial Rating (90 million revolutions) <sup>5</sup>             | 6180 lbf      |
| C1 - Dynamic Radial Rating (1 million revolutions) <sup>6</sup>               | 23800 lbf     |
| C0 - Static Radial Rating   | 33500 lbf     |
|   |               |



## Shandong Xiangyue bearing Trading Co....

|   |          |
|---|----------|
| $C_{a90}$ - Dynamic Thrust Rating (90 million revolutions) <sup>7</sup> | 4500 lbf |
| K - Factor <sup>8</sup>   | 1.37     |
| G1 - Heat Generation Factor (Roller-Raceway)                            | 60.1     |
| G2 - Heat Generation Factor (Rib-Roller End)                            | 24.5     |
| Cg - Geometry Factor  | 0.103    |