



# Shandong Xiangyue bearing Trading Co....



## SKF Ball Baring 6208 6209 6210 Zz 2RS with High Quality

Bearing No. 6208

6208 Bearing 2D drawings and 3D CAD models

|                               |                          |
|-------------------------------|--------------------------|
| Size                          | 40x80x18 mm              |
| Bore Diameter                 | 40 mm                    |
| Outer Diameter                | 80 mm                    |
| Width                         | 18 mm                    |
| d                             | 40 mm                    |
| D                             | 80 mm                    |
| B                             | 18 mm                    |
| C                             | 18 mm                    |
| d1                            | 52,6 mm                  |
| r1 min.                       | 1,1 mm                   |
| r2 min.                       | 1,1 mm                   |
| D1                            | 67,4 mm                  |
| D2                            | 69,8 mm                  |
| da min.                       | 47 mm                    |
| Da max.                       | 73 mm                    |
| rc max.                       | 1 mm                     |
| Weight                        | 0,37 Kg                  |
| Basic dynamic load rating (C) | 32,5 kN                  |
| Basic static load rating (C0) | 19 kN                    |
| Fatigue load limit (Pu)       | 0,8                      |
| Reference speed               | 18000 r/min              |
| Limiting speed                | 11000 r/min              |
| Calculation factor (f0)       | 14                       |
| Category                      | Single Row Ball Bearings |
| Inventory                     | 7.0                      |



## Shandong Xiangyue bearing Trading Co....

|                                 |  |
|---------------------------------|--|
| Manufacturer Name               | SKF  |
| Minimum Buy Quantity            | N/A  |
| Weight / Kilogram               | 0.367  |
| EAN                             | 7316577086297  |
| Product Group                   | B00308   |
| Enclosure                       | Open   |
| Precision Class                 | ABEC 1   ISO P0  |
| Maximum Capacity / Filling Slot | No   |
| Rolling Element                 | Ball Bearing   |
| Snap Ring                       | No   |
| Internal Special Features       | No   |
| Cage Material                   | Steel  |
| Internal Clearance              | C0-Medium  |
| Inch - Metric                   | Metric   |
| Long Description                | 40MM Bore; 80MM Outside Diameter; 18MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category                        | Single Row Ball Bearing  |
| UNSPSC                          | 31171504   |
| Harmonized Tariff Code          | 8482.10.50.68  |
| Noun                            | Bearing  |
| Keyword String                  | Ball   |
| Manufacturer URL                | <a href="http://www.skf.com">http://www.skf.com</a>  |
| Manufacturer Item Number        | 6208   |
| Weight / LBS                    | 0.81   |
| Outer Race Width                | 0.709 Inch   18 Millimeter   |
| Outside Diameter                | 3.15 Inch   80 Millimeter  |
| Bore                            | 1.575 Inch   40 Millimeter   |
| d <sub>1</sub>                  | 52.6 mm  |
|                                 |  |



## Shandong Xiangyue bearing Trading Co....

|                                |         |
|--------------------------------|---------|
| $D_2$                          | 69.8 mm |
| $r_{1,2}$ min.                 | 1.1 mm  |
| $d_a$ min.                     | 47 mm   |
| $D_a$ max.                     | 73 mm   |
| $r_a$ max.                     | 1 mm    |
| Basic dynamic load rating C    | 32.5 kN |
| Basic static load rating $C_0$ | 19 kN   |
| Fatigue load limit $P_u$       | 0.8 kN  |
| Calculation factor $k_r$       | 0.025   |
| Calculation factor $f_0$       | 13.8    |
| Mass bearing                   | 0.36 kg |